

Volta Drills 165.3m of 1.36% Total Rare Earth Oxides (“TREO”) and 81.3 g/t Gallium Oxide at Springer

written by Raj Shah | October 1, 2026

Including 2.95m at 7.54% TREO and 283 g/t gallium oxide, the highest-grade intercept of the 2026 drill program

HIGHLIGHTS

- **New highest-grade intercept of the 2026 program.** SL26-29 returned 2.95m of 7.54% TREO and 282.7 g/t Ga_2O_3 .
- **Thick, high-grade mineralized core.** SL26-29 returned 165.3m of 1.36% TREO and 81.3 g/t Ga_2O_3 , while SL26-30 returned 109.5m grading 1.33 % TREO and 85.0 g/t Ga_2O_3 .
- **Mineralization remains open at depth and beyond the conceptual open pit.** SL26-29 ended in mineralization more than 400m below surface, with a sample near the bottom of the hole returning 1.97% TREO and 101.6 g/t Ga_2O_3 . The hole also extends mineralization 190m beyond the eastern limit of the conceptual open pit.
- **Significant dysprosium and terbium enrichment.** SL26-30 returned 26.8m grading 1.95% TREO and 104.6 g/t Ga_2O_3 (114.2m – 141.0m). Within it, heavy rare earths make up 18.2% of TREO over 3.0m (127.5m – 130.5m), including 278 g/t Dy_2O_3 and 44 g/t Tb_4O_7 , both critical inputs for high-performance permanent magnets.
- **Continuous gallium mineralization provides additional upside.** Gallium occurs throughout the full assayed lengths

of SL26-29 and SL26-30, and is not included in the current Springer mineral resource estimate.

October 1, 2026 ([Source](#)) – **Volta Metals Ltd. (CSE: VLTA) (OTCQB: VOLMF) (FSE: D0W)** (“Volta” or the “Company”) announces assay results from drill holes SL26-29, SL26-30 and SL26-38, completing the 13-hole 2026 winter drill program at its Springer Rare Earth Element deposit (the “Property”), near Sturgeon Falls, Ontario, Canada.

Drill holes SL26-29 and SL26-30 tested the core of the deposit, averaging about 1% TREO over 351.0 metres (“m”) and 286.5m, respectively, with gallium mineralization present throughout the full assayed lengths. SL26-29 also returned the highest-grade rare earth and gallium intercept of the 2026 program, while SL26-30 intersected a zone enriched in the high-value heavy rare earth elements dysprosium and terbium. See Tables 1 to 3 for details.

“SL26-29 has raised the bar again in the heart of Springer, returning 7.54% rare earth oxides and 283 g/t gallium oxide over 2.95m within a 165.3-metre interval grading 1.36% TREO. Importantly, the drill hole remained strongly mineralized at depth, with a sample near the bottom of the hole returning nearly 2% TREO more than 400m below surface. SL26-30 highlights another important dimension of the Springer system – intersecting enrichment in dysprosium and terbium, two critical heavy rare earths used in high-performance permanent magnets. Both drill holes average approximately 1% rare earth oxides over roughly 290m to 350m, with more than 30 g/t gallium oxide in every sample,” said Kerem Usenmez, President and CEO of Volta.

WHY THESE RESULTS MATTER

- **Grade within a large deposit.** Springer is among the top 10 largest rare earth deposits in North America (S&P Global Market Intelligence, 2025). SL26-29 and SL26-30 both cut the centre of the deposit and returned about 1% TREO over hundreds of metres, and SL26-29 extends mineralization beyond the conceptual open pit.
- **Magnet metals.** Neodymium and praseodymium are the main rare earths in permanent magnets, and dysprosium and terbium keep those magnets working at high temperatures. These magnets are used in electric vehicle motors, wind turbines and defence systems.
- **Gallium.** Gallium is used in semiconductors for power, electronics, and radar. China produces most of the world's gallium and restricts its export. Springer's gallium is not included in the current mineral resource estimate.

Table 1: Selected assay highlights from drill holes SL26-29, SL26-30 and SL26-38, Springer Rare Earth Deposit.

Drill Hole No.	From (m)	To (m)	Interval (m)	TREO (%)*	Ga₂O₃ (g/t)**	% Magnet REO of TREO***
SL26-29	7.50	420.00	412.50	0.852	64.4	25.0
	including					
SL26-29	69.00	420.00	351.00	0.965	68.6	23.8
	131.70	297.00	165.30	1.363	81.3	23.1
	195.00	286.50	91.50	1.683	91.8	20.8
	249.00	304.50	55.50	1.797	100.3	20.1
	249.00	286.50	37.50	2.272	114.9	19.5
	249.00	251.95	2.95	7.537	282.7	16.6
	276.00	280.50	4.50	3.075	138.2	17.7

Drill Hole No.	From (m)	To (m)	Interval (m)	TREO (%)*	Ga ₂ O ₃ (g/t)**	% Magnet REO of TREO***
	417.00	418.50	1.50	1.971	101.6	20.1
SL26-30	5.40	351.00	345.60	0.869	67.6	24.0
	including					
	25.50	312.00	286.50	0.989	72.3	24.4
	79.50	189.00	109.50	1.328	85.0	21.3
	79.50	88.50	9.00	1.574	77.1	20.9
	114.20	141.00	26.80	1.952	104.6	19.8
	130.50	133.50	3.00	2.931	136.4	18.9
	151.50	189.00	37.50	1.365	93.9	21.5
	282.00	312.00	30.00	0.871	72.6	24.8
SL26-38	6.00	357.00	351.00	0.359	36.3	22.9
	including					
	248.30	337.50	89.20	0.526	39.8	20.8
	301.50	309.00	7.50	1.454	63.5	19.8

Rows marked "including" are higher-grade sections within the interval above them.

True thickness/width of mineralization is unknown; intervals are reported as downhole core lengths.

*TREO (%) = La₂O₃ + CeO₂ + Pr₆O₁₁ + Nd₂O₃ + Sm₂O₃ + Eu₂O₃ + Gd₂O₃ + Tb₄O₇ + Dy₂O₃ + Ho₂O₃ + Er₂O₃ + Tm₂O₃ + Yb₂O₃ + Lu₂O₃ + Y₂O₃ (%).

**Ga₂O₃ (g/t) is calculated from assayed gallium (Ga) ppm using the stoichiometric factor 1.3442.

***% Magnet REO = (Pr₂O₃ + Nd₂O₃ + Tb₂O₃ + Dy₂O₃) / TREO x 100. Pr₂O₃ and Tb₂O₃ are derived from assayed Pr (ppm) and Tb (ppm) using stoichiometric conversion factors of 1.2082 and 1.1762, respectively.

DETAILS

The following sections summarize results from each hole, with assay highlights presented in Table 1. At Springer, rare earth and gallium mineralization is consistently associated with white dolomite-carbonatite veins.

SL26-29: Highest Grade intercept of the 2026 Program and Mineralization Remains Open at Depth

SL26-29 was drilled through the centre of the Springer deposit and the high-grade resource shell (Figure 2). The hole indicates good to excellent mineral continuity within the core of the deposit and extends rare earth and gallium mineralization approximately 190m beyond the eastern limit of the current conceptual resource open pit.

SL26-29 was continuously assayed from 7.5m to 420.0m, returning an average of 0.85% TREO and 64.4 g/t Ga_2O_3 over 412.5m – see Table 1 for details. Higher-grade intervals include 91.5m grading 1.68% TREO and 91.8 g/t Ga_2O_3 (from 195.0m – 286.5m), 55.5m grading 1.80% TREO and 100.3 g/t Ga_2O_3 (from 249.0m – 304.5m) and 7.54% TREO and 282.7 g/t Ga_2O_3 over 2.95m (249.0m – 251.95m), including 7.67% TREO and 297.1 g/t Ga_2O_3 over 1.45m (250.5m – 251.95m). The 2.95m interval also contains 3.90% CeO_2 , 2.18% La_2O_3 and 1.25% Magnet 4 ($\text{Pr}_2\text{O}_3 + \text{Nd}_2\text{O}_3 + \text{Tb}_2\text{O}_3 + \text{Dy}_2\text{O}_3$), the four rare earth oxides principally used in high-performance permanent magnets. In the highest-grade intervals, cerium and lanthanum make up most of the rare earth content, so magnet rare earths form a lower share of TREO (Table 1) even though their absolute grade is higher.

Within the centre of the deposit, rare earth and gallium mineralization is associated with two principal textures:

- Zoned syenite, where grey prismatic crystals are rimmed by red K-feldspar, with carbonatite filling the spaces between them. Examples occur at 195.0m – 196.5m, 207.0m – 208.5m and 225.0m – 226.5m.
- Vuggy (cavity-rich) carbonatite veins with abundant hematite, including intervals at 198.0m – 199.5m and 205.5m – 207.0m.

A sample near the bottom of the hole (417.0m – 418.5m) returned 1.97% TREO and 101.6 g/t Ga_2O_3 in red syenite with carbonatite veins. Because SL26-29 was drilled at a dip of -85° , this sample lies more than 400m below surface. The result is consistent with a vertically extensive carbonatite-hosted system that remains open at depth.




Figure 2. Cross section for drill hole SL26-29.

To view an enhanced version of this graphic, please visit:

https://images.newsfilecorp.com/files/9598/316790_740e40b934c48b

[f5_001full.jpg](#)

SL26-30: averages 0.87% TREO and 67.6 g/t Ga_2O_3 over 345.6m, including 26.8m of 1.95% TREO and a Heavy Rare Earth Enriched Zone

Similar to SL26-29, SL26-30 passes through the centre of the Springer deposit and infills between drill holes SL11-02, SL11-04 and SL12-08 (Figure 4).

SL26-30 was continuously assayed from 5.4m to 351.0m and averages 0.87% TREO and 67.6 g/t Ga_2O_3 over 345.6m. The highest-grade zone is 26.8m grading 1.95% TREO and 104.6 g/t Ga_2O_3 (114.2m – 141.0m, Figure 3).

Heavy rare earths. From 127.5m to 130.5m, heavy rare earth oxides make up 18.2% of TREO, with 278 g/t Dy_2O_3 and 44 g/t Tb_4O_7 over 3.0m grading 1.50% TREO (Table 2). A wider 9.0m interval (121.5m – 130.5m) grades 238 g/t Dy_2O_3 , 1.78% TREO and 97.95 g/t Ga_2O_3 . Dysprosium is valued principally for its use in high-performance permanent magnets.




Figure 3. SL26-30 high-grade TREO and Ga mineralization in red syenite and white carbonatite, 130.5m – 144.1m, boxes 32–34.

To view an enhanced version of this graphic, please visit:

https://images.newsfilecorp.com/files/9598/316790_740e40b934c48bf5_002full.jpg




Figure 4. Cross section for drill hole SL26-30.

To view an enhanced version of this graphic, please visit:

https://images.newsfilecorp.com/files/9598/316790_740e40b934c48bf5_003full.jpg

SL26-38: Infill Drilling in the South Part of the Deposit

SL26-38 intersects the southern portion of the Springer deposit (Figure 5). It infills between drill holes SL12-20 and SL12-17, passing through syenite and ending in granitic gneiss. The drill hole averages 0.36% TREO and 36.3 g/t Ga_2O_3 over 351.0m (6.0m – 357.0m), including 89.2m grading 0.53% TREO and 39.8 g/t Ga_2O_3 (248.3m – 337.5m).




Figure 5. Cross section for drill hole SL26-38.

To view an enhanced version of this graphic, please visit:

https://images.newsfilecorp.com/files/9598/316790_740e40b934c48bf5_004full.jpg

Table 2: Heavy rare earth highlight intervals, SL26-29, SL26-30 and SL26-38, Springer.

Drill Hole No.	From (m)	To (m)	Interval (m)	TREO (%)	Dy ₂ O ₃ (g/t)	Tb ₄ O ₇ (g/t)	% HREO of TREO*
SL26-30	127.5	130.5	3.0	1.50	278	44	18.2
SL26-30	121.5	132.0	10.5	2.00	231	39	11.3
SL26-29	249.0	251.95	2.95	7.54	141	42	1.9
SL26-38	301.5	304.5	3.0	1.81	72	15	3.5

*HREO (%) = Gd₂O₃ + Tb₄O₇ + Dy₂O₃ + Ho₂O₃ + Er₂O₃ + Tm₂O₃ + Yb₂O₃ + Lu₂O₃ + Y₂O₃ (%). % HREO of TREO = HREO / TREO x 100. Dysprosium

(Dy₂O₃) and terbium (Tb₄O₇) are highlighted separately as the two rare earth oxides most valued for high-performance magnet applications.

Table 3: Springer drill hole collar locations. UTM NAD 83, Zone 17.

Drill Hole No.	Easting (m)	Northing (m)	Elevation (m)	Azimuth (°)	Dip (°)	Length (m)
SL26-29	580760	5143738	250.4	270	-85	420
SL26-30	580741.07	5143777.97	248.47	267	-45	351
SL26-38	580703.12	5143436.05	249.71	270	-45	357

Azimuth and dip are collar orientations. No downhole directional survey was completed.

NEXT STEPS AND UPCOMING MILESTONES

With these latest results, assays for all 13 drill holes of the 2026 winter drill program at Springer have been received and released.

Volta is targeting completion of two mineral resource estimates for Springer in the fourth quarter of 2026:

- **Initial gallium mineral resource estimate.** Subject to confirmatory metallurgical test results, currently in progress, this would be the first gallium resource declared for the Property.
- **Updated rare earth mineral resource estimate.** This will incorporate the 2026 infill and expansion drilling, including the high-grade results from SL26-29 and SL26-30 reported today.

Both estimates would be prepared in accordance with National

Instrument 43-101 and CIM Definition Standards.

The Company cautions that the timing of both mineral resource estimates depends on the completion of supporting metallurgical and analytical work and on the availability of the Company's independent consultants. There is no assurance that either estimate will be completed within the anticipated timeframe, that a gallium mineral resource will be defined at all, or that any updated rare earth mineral resource estimate will be larger or higher grade than the current MRE. Mineral resources are not mineral reserves and do not have demonstrated economic viability.

RESOURCE ESTIMATE

On February 23, 2026, Volta reported an updated Mineral Resource Estimate ("MRE") for the Springer deposit, effective December 31, 2025, prepared by SLR Consulting (Canada) Ltd. The MRE comprises 56.6 Mt Indicated at 0.70% TREO (including a near-surface high-grade core of 11.5 Mt at 1.10% TREO) and 119.5 Mt Inferred at 0.58% TREO (including a near-surface high-grade core of 3.0 Mt at 1.16% TREO). Resources are reported within an optimized open pit shell above a C\$43/t net metal revenue cut-off. Revenue is driven primarily by praseodymium and neodymium, which together account for approximately 90% of total net metal value. The MRE placed Springer among the top 10 largest REE deposits in North America based on the S&P Global Market Intelligence database (2025). The Company cautions that mineral resources are not mineral reserves and do not have demonstrated economic viability.

Mineralization remains open in all directions. Gallium is not included in the current MRE and will be reported separately. An NI 43-101 Technical Report supporting the MRE was filed on SEDAR+ on April 9, 2026.

QA/QC PROTOCOL

All drilling was completed by a diamond drill rig producing NQ-size core. Volta implemented a strict QA/QC protocol in processing all rock samples collected from the diamond core obtained from the Springer property. The protocol included inserting reference materials, in this case high-concentration and low-concentration certified rare earth element and gallium standards, blanks, and drill core duplicates, to validate the accuracy and precision of the assay results. All collected rock core samples were cut in half by a rock saw, placed in sturdy plastic bags and zip-tied shut while under the supervision of a professional geologist. The remaining half core was returned to the core box, which is stored on the Property. The samples were shipped from Volta's core shack in Sturgeon Falls to the Saskatchewan Research Council's ("SRC") facility in Saskatoon, Saskatchewan, using the Manitoulin Transport freight shipping company.

The drill core samples were analyzed at SRC using lithium metaborate fusion with subsequent analysis by ICP-MS. SRC holds ISO/IEC 17025:2017 accreditation from the Standards Council of Canada ("SCC"). Syenite standard SY-5 from Natural Resources Canada was inserted by SRC in the sample stream for every 20 drill core samples. Standard SY-5 passed within two standard deviations for rare earth elements (La to Lu) and Ga. All internal standards and duplicates, and all external blanks, standards and core duplicates, passed a Quality Control review by the Qualified Person.

QUALIFIED PERSON

The technical content of this press release has been reviewed and approved by Dr. Julie Selway, P.Geo., VP, Exploration, and Qualified Person ("QP") as defined in National Instrument

43-101, Standards of Disclosure for Mineral Projects.

ABOUT VOLTA METALS LTD.

Volta Metals Ltd. (CSE: VLTA) (FSE: D0W) (OTCQB: VOLMF) is a critical mineral exploration company focused on rare earths, gallium, lithium, cesium, and tantalum. Volta owns, has optioned, and is currently exploring a critical minerals portfolio of rare earth, gallium, lithium, cesium, and tantalum projects in Ontario, one of the world's most prolific and emerging hard-rock critical mineral districts.

Volta is advancing its 4,750-hectare Springer REE Deposit, located on the traditional territory of the Nipissing First Nation in Sturgeon Falls. The Springer Rare Earth Element deposit sits approximately 70 km east of Sudbury, Ontario, with direct access via the Trans-Canada Highway and Highway 64. The project benefits from well-developed infrastructure, including paved road access, on-site power lines fed from the Crystal Falls hydroelectric dam, a natural gas pipeline, and Canadian National Railway service, all within 8 km of the deposit.

To learn more about Volta and its Springer and Aki Projects, please visit www.voltametals.ca.

ON BEHALF OF THE BOARD

For further information, contact:

Kerem Usenmez, President & CEO

Tel: 416.919.9060 | Email: info@voltametals.ca | Website: www.voltametals.ca

Neither the CSE nor the Canadian Investment Regulatory Organization (CIRO) accepts responsibility for the adequacy or accuracy of this release.

This news release contains forward-looking statements relating

to exploration activities, plans, strategies, and other statements that are not historical facts. Forward-looking statements are often identified by terms such as “will”, “may”, “should”, “anticipate”, “expects”, “targeting” and similar expressions. All statements other than statements of historical fact included in this news release are forward-looking statements that involve risks and uncertainties. Forward-looking information in this news release includes, but is not limited to, the Company’s stated intention and timing to complete a maiden gallium mineral resource estimate and an updated rare earth mineral resource estimate for the Springer deposit in the fourth quarter of 2026, statements regarding the potential extent and grade of the gallium and rare earth mineralized envelopes, including the heavy rare earth enrichment observed in SL26-30 and the potential for mineralization to continue at depth and beyond the proposed open pit, the geological interpretation of the Springer REE deposit as a vertically extensive carbonatite system, statements regarding gallium market conditions and Chinese export control measures, and the potential for the 2026 drilling program to support future resource estimation. There can be no assurance that such statements will prove to be accurate, and actual results and future events could differ materially from those anticipated. Important factors that could cause actual results to differ materially from the Company’s expectations include the risks detailed from time to time in the filings made by the Company with securities regulators, the future prices and demand for rare earth elements and gallium, changes to export control or trade measures affecting gallium supply, the absence to date of metallurgical test work demonstrating that gallium can be economically recovered from the Springer mineralization, laboratory results that differ from visual or geological observations, and delays or the inability of the Company to obtain any necessary approvals, permits and authorizations

required to carry out its business plans. The reader is cautioned not to place undue reliance on any forward-looking statements. Forward-looking statements contained in this news release are made as of the date of this news release, and the Company disclaims any intention or obligation to update or revise any forward-looking statements, whether as a result of new information, future events, or otherwise, other than as required by law.